

BC43


The Ultimate Benchtop Confocal Microscope

Key Features

- ✓ Benchtop multimodal imaging system
- ✓ Instant confocal: Blur-free imaging
- ✓ Widefield imaging
- ✓ Differential phase contrast & brightfield
- ✓ Borealis uniform illumination
- ✓ GPU-powered deconvolution

Key Applications


- ✓ Cell biology
- ✓ Developmental biology
- √ Neuroscience
- Cancer biology
- ✓ Tissue imaging
- ✓ Organoids & large organisms




Andor Benchtop Confocal


2D and 3D imaging as easy as ABC
















Andor Benchtop Confocal

Total Imaging Flexibility

Confocal Imaging

Confocal technology provides **high-contrast**, **blur-free images**. It boosts image quality of thin samples, such as monolayer cultures, and is especially suited for thick samples like small model organisms, 3D cultures and cleared tissues.

BC43 captures images at **least 10x faster than point scanning confocals**, boosting productivity, yet maintaining full resolution. Image deeper with higher quality than solutions that rely on computational clearing or deconvolution alone.

Until now confocal has been too expensive and complex for many. BC43 is revolutionary – a confocal at the heart of your lab at an **affordable price with no expertise required**!

✓ Widefield Imaging

With such easy access to confocal why use widefield imaging? Widefield is appropriate especially for thin samples, where it can provide greater sensitivity and higher speeds, resulting in an increase in productivity and temporal resolution. Combine with deconvolution for resolution comparable to a confocal image. Examples of suitable samples are tissue sections or micro-organisms.

✓ Transmitted Light Imaging

BC43 offers two transmitted light options: **brightfield** for samples with inherent contrast like larger organisms, and **Differential Phase Contrast (DPC)**, that can be applied for samples which deliver high and low contrast.

You can even **combine image modes** for even greater imaging flexibility! For example, combine DPC with widefield or confocal imaging modalities.

•••

Application Focus

Developmental Biology

BC43 cuts through the challenges easily, spanning development from the first rounds of cell division to the fully developed organism. Use BC43 to image at depth, in gentle live imaging experiments of cells and tissues. Effortlessly acquire multiple Z stacks, multiple tiles in combination with time-lapse imaging.

Extract sharp 2D images or instantly explore stunning 3D volumes in a fraction of the time you're used to.

BC43 delivers fast high-resolution imaging of developing model organisms (e.g. zebrafish and drosophila). Imaging deeper than conventional fluorescence microscopes and delivering a 10-fold more productive experience than a traditional confocal. No sacrificing sensitivity, resolution or 3D detail for speed, or to avoid bleaching.

BC43 features for development biology:

- ✓ Fast high resolution imaging.
- ✓ Image deep in both live and fixed samples.
- Montage & seamless stitching at any level of magnification.



Application Focus


Cell Biology

Working closely with leading cell biologists we have carefully developed BC43 to meet the needs of a broad range of experiments. Reveal the detail inside cells from nm to mm within tissues and whole model organisms with BC43. Use BC43 in confocal mode to see detail hidden in the sample background or image in widefield to increase sensitivity and speed.


Image fast dynamic events, such as microtubule dynamics, or study longer processes like cell cycle over 24 hours with no photobleaching or phototoxicity.

BC43 features for cell biology:


- ✓ Image long processes.
- ✓ Image fast dynamic events.
- ✓ No photobleaching or phototoxicity.
- ✓ nm to mm imaging capability.



Zebrafish fin in the process of bone regeneration. Image shows the perfect stitching of 4 imaging fields, using three channels and 51 stacks for each field, covering a Z range of 174 µm. Newly formed bony tissue in purple (calcein staining) and cathepsin k+ cells (the osteoclasts) in yellow, DNA is in Cyan. Image credits: Alessio Carletti, Universidade do Algarve.




Mammalian cell in prophase. Image was acquired using BC43 confocal mode, using 4 acquisition channels and covering 10 µm Z range at Nyquist. Image was further deconvolved and rendered in Imaris. Dark blue – actin, yellow – microtubules, magenta – mitochondria, cyan-DNA. Image credits: Claudia Florindo, Andor Technology.



Cell division. Mammalian cells imaged with BC43 using confocal imaging mode for over 4 h. At each time point, 4 independent positions were imaged and for each position 3 channels and 15 Z stacks acquired. Images from one of the 4 positions. Cells undergoing mitosis during the course of the imaging. Red-actin, yellow-microtubules, DNA-cyan.

Image credits: Ines Baião-Santos and Álvaro Tavares, Universidade do algarve, Claudia Florindo, Andor Technology.

•••



Application Focus


Tissue Imaging

Large area imaging needs to provide both cellular resolution and the full organ context. The advanced high-speed technology in BC43 means you no longer need to compromise. Large area tissue confocal imaging is now possible. Ten times faster than regular confocals. No sacrifices in resolution, or field of view. BC43 delivers results fast, shortening the time to publication.

Discover more in intact tissues, use cleared samples and BC43 in confocal mode to image even thicker samples. BC43 takes advantage of the working distance of modern objectives: imaging hundreds of microns at high magnifications, and beyond.

BC43 features for tissue imaging:

- Fast confocal and low light widefield imaging.
- ✓ Seamless large tissue imaging for fixed and live sample.
- ✓ Image from nm to mm.



Zebrafish intestine stitched image. Image was acquired using the confocal imaging modality of BC43, with 4 imaging channels, 77 stacks and 28 tiles. The full stitched image is composed of a total of 15092 images. The deconvolution and stitching options were both activated on the protocol. Sample courtesy of Julien Resseguier, at NorMic, University of Oslo. *Image credits: Claudia Florindo, Andor Technology.*

BC43 for Core Facilities

Small in size, Big in performance

BC43 is an ideal instrument for a core facility, easy to operate, with multiple microscopy techniques. It provides great images fast, whatever the sample. Free up your more complex imaging systems for users doing highly specialised experiments.

Many imaging systems can be difficult for users to get comfortable using without extensive training. BC43 is intuitive and easy for even novice microscopists to master. Simple operating procedures, and minimal maintenance allow exceptional productivity from the system. This means less time training, more time imaging and more time for core staff running the facility.

BC43 features for core facilities:

- ✓ Low maintenance.
- ✓ Fast to learn, easy to use, minimal support.
- Application versatility.




Image right: Whole-body flatfish at climax of development.

Fish was stained with acetylated tubulin (Yellow) and myosin heavy chain (blue). Image acquired with BC43 using multiple tile acquisition and montage. 30 tiles acquired to compose the image. Each tile had 175 slices, over a Z range of 521 μm . Image credits: Marco Campinho, CBMR Universidade do Algarve and Claudia Florindo,



Anaphase in mammalian cells. Image shows a MIP of an anaphase

Integrated Software Solutions

Fusion

BC43 has an integrated, easy-to-use, and accessible software interface that delivers high-end imaging. Users benefit from easy protocol set up for multidimensional experiments, such as one-click multi-position-montage and multiwell integration with an intuitive user interface and workflow for protocol set up.

BC43 Fusion delivers real-time GPU-based deconvolution increasing the resolution of the image. Seamlessly integrated into the hardware, the in-line 3D stitching allows the full montage and visualisation of multiple tiles integrated into the context of the whole organism.

Imaris®

BC43 saves files in the Imaris IMS file format, permitting easy transfer of data into Imaris. Imaris for BC43 is included for isosurface rendering, high resolution snapshots, creation of multi-dimensional movies and downstream image editing. Additional application-specific modules of Imaris are available and include options for adding measurements suited for cell & developmental biologists, neuroscientists and many more disciplines within life sciences.

To find out more about Imaris please see: <u>imaris.oxinst.com</u>

cell Image credits: Álvaro Tavares, Ines Baião-Santos, CBMR Universidade

do Algarve and Claudia Florindo, Andor Technology.

Simple Workflows

Fast to learn & time saving


Here we show two possible workflows. All options can be performed in combination.

Z Stack

Add Z stack for 3D image.

Step 1

Select the area of sample to be imaged.



Step 2


Select required objective.

Set centre of Z scan.

Press Acquire.




Result



Multi-position

Step 1

Snap or overview the sample and move to the desired objective.




Step 2

Select the positions to be imaged.

Press Acquire.



Result



Key Features of BC43

Hardware Feature	Benefit
High-speed confocal imaging	 ✓ 3D optical sectioning with high background rejection. Eliminates blur. ✓ Allows deep and large tissue imaging at speed for higher productivity. ✓ Image fast dynamic events in thicker samples.
Widefield imaging	 ✓ Image thin specimens/structures that do not require optical sectioning. ✓ Highest sensitivity mode for samples super-sensitive to light, or to detect the weakest fluorophores signals.
Benchtop system	 ✓ No need for a dark room. Fits in a small bench space in the laboratory. ✓ Set up experiments and image immediately.
Built-in anti-vibration mechanism	Ensures optimal image quality on your benchtop confocal when working at high-magnification and live-cell time-series.
2x objective for quick sample overview	 Quickly navigate your sample with an overview montage and select area to image.
3D ergonomic joystick	Efficient sample navigation, position and focus with adjustable navigation and focus speeds.
Patented Borealis illumination	 Optimises illumination uniformity for seamless stitching and more accurate cross-field analysis.
Total imaging flexibility	 ✓ Image multiple fluorescent channels confocal and/or widefield. ✓ Capture multiple imaging modalities in one protocol; fluorescence with brightfield and Differential Phase Contrast.
Differential phase contrast	 ✓ Capture label-free images. ✓ High contrast Andor transmitted light imaging modality.
sCMOS detector	 High sensitivity detector for short exposures and reduced photobleaching. Maximise number of cells in a single image and capture large samples efficiently with a large field of view e.g. image a 1.84 mm diagonal with 10x objective. High dynamic range - capture weak and bright signals in a single image without saturation.


Software Feature	Benefit
Fusion for BC43	 ✓ Fast to learn and easy-to-use multidimensional acquisition software. ✓ Integrated confocal, widefield and brightfield imaging options. ✓ Post-acquisition processing with stitching and deconvolution.
Easy workflow	 From sample insertion to image acquisition. Add sample, find sample, set bounds, and acquire the image. No expertise required. Quick montage - Faster acquisition and experimental setup, improve productivity. Quick 3x3 sample overview, easy to set sample bounds, and center sample for image acquisition with one-click.
Patented Focus Seek & Lock	 ✓ Focus Seek - makes focusing on your sample easier. ✓ Focus Lock - maintains sample focus during long time-lapse and large sample acquisitions.
Multidimensional acquisition	 Acquire multiple imaging dimensions to visualise all the sample features—simultaneous acquisition of time, Z and tile positions.
Multiposition	 Acquire multiple positions in a sample and maximise throughput from a single experiment. Multiposition montage - Acquire multiple montages at independent positions and maximise throughput on fixed or live cell experiments.
Montage & Stitching	 ✓ Automatically capture large sample data bigger than the field of view. ✓ Stitch huge sample montages in 2D and 3D for the full picture.
Multiwell	Allow multiwell imaging for 6, 12, 24, and 96 well plates—image different treatment, phenotypes, drug screening experiments, etc.
Real-time 3D-rendering	✓ Immediate visual feedback on experimental progress to evaluate data and make appropriate decisions in real-time.
Clearview-GPU™ accelerated deconvolution	 ✓ Increase image resolution and contrast with deconvolution. ✓ Up to 50x faster processing than non-GPU based deconvolution solutions.
Imaris for BC43	 Visualise your 2D/3D/4D images in the world's leading interactive microscopy image analysis software. Generate isosurface reconstructions for better interpretation and presentation of raw images. Create high resolution snapshots and multi-dimensional movies with ease.


Specifications¹

Microscope Unit	BC43
Imaging Modes	High-speed confocal Widefield epifluorescence Transmitted light - brightfield and Differential Phase Contrast
Imaging Methods	Single color, multicolor, z-stacking (volume), time-lapse, multi-position, multi-well, montage and 2/3D stitching.
ClearView™ GPU	Clears image of non-specific sample background signal and improves resolution beyond the normal optical limits.
Camera	
Resolution	6.5 µm pixel; 2048x2000 pixels (4.1 MP)
QE*2	Up to 82%
Field of view (mm)	18.4 mm (diagonal)
Cooling	0°C
Images	16-bit, monochrome
Illumination	
Fluorescence	4 fixed wavelengths of 405 nm, 488 nm, 561 nm, 638 nm
Transmitted light	Broad spectrum visible light LED
Optics (Objectives)	
Objective Lens Nosepiece	Motorised 5 position turret
Objective Magnifications	BC43 is supplied with 2x objective for sample overview. Select additional objectives from 10x to 60x magnification.
Precision motorised x,y stage	Travel Range = 110 mm x 80 mm Resolution = 100 nm
Z-Control & Focus	Range = 14.5 mm
Autofocus "Seek & Lock" Technology	Sample "Seek & Lock". Finds focal plane for new sample and maintains focus stability during time-lapse experiments.
Sample Vessels Supported	Glass slides (25 by 75 mm); culture dish (35 mm diameter); Multiwell plates (6, 12, 24 & 96); Multiwell chamber coverslip (2, 4, 8).
Incubation (option)	Stage-top incubator. Sliding lid for easy sample access and exchange. Objective heater for oil-immersion objectives.
Workstation	
PC	Windows™ 10 software 64 GB DDR4 RAM 512 GB PCIe SSD Boot drive 4 GB Graphics Card 2 TB Image Data storage (option to add more)
Monitor	24 inch

Mechanical Drawings

Units: Millimeters [Inches]





Creating the Optimum Product for you

Please contact your local sales representative who will be able to guide you through the ordering process.

Step 1.	Choose the model	
	Description	Order Code
BC43 Unit	Andor BC43 Benchtop Confocal Microscope. Equipped with: ■ Brightfield and Differential Phase Contrast transmitted white light illumination for label-free visualisation and imaging, widefield epifluorescence for low-light imaging and microlens based spinning disk confocal for fast high-contrast high-quality 3D imaging. ■ Built-in vibration management to support use on a regular laboratory bench or sturdy table. ■ Patented Focus Seek and Lock to aid sample focus and to retain focus during time-lapse experiments. ■ 2x objective included to aid sample navigation. 4 further positions available on the motorized turret to add objectives appropriate to your needs. Support up to 60x (choose from recommended list). ■ Excitation lines 405 nm, 488 nm, 561 nm & 638 nm, and emission filter for imaging commonly used fluorophores such as DAPI, Alexa 488/GFP, Alexa 546/mCherry/TRITC, CY5/Alexa Fluor 640. ■ Motorised x.y and z axis sample positioning via joystick or software interface. ■ 4.1 MP (6.5 µm pixel, 16-bit) monochrome camera with up to 82% QE. 18.4 mm diagonal field of view. ■ Control software to capture multi-dimensional experiments in x.y.z., time, multiposition, multi-well and montage capture with 2/3D stitching. Includes ClearView GPU™ for super-resolution images with reduced sample background for optimal quality imaging. ■ Workstation includes Motherboard: 6 Core, 12 M cache, base 3.3 GHz, up to 4.8 GHz, DDR4-2666. 64 GB RAM. ■ 512 GB PCIe NVMe Class 40 M.2 SSD Boot drive, 4 GB Graphics Card, 2 TB image data storage. ■ Imaris for BC43, downstream image editing, isosurface rendering, high resolution	Order Code INS-BTCF
	snapshots and creation of multi-dimensional movies.*3	

Step 2.	Workstation upgrade options	
1	Description	Order Code
	Data storage upgrade for supplied PC workstation. Up to two additional 4 TB drives can be added.	INS-PC-DRV-4TB
Options		

Select the required objectives Step 3. Description Order Code 10x Plan Fluorite objective with 0.3 numerical aperture. Working distance of 16 mm. INS-OBJ-10-030 10x Plan Apochromat objective with 0.45 numerical aperture. Working distance of 4 mm. INS-OBJ-10-045 20x Plan Apochromat objective with 0.75 numerical aperture. INS-OBJ-20-075 Working distance of 1 mm. 40x Plan Fluorite Objective with 0.75 numerical aperture. INS-OBJ-40-075 Working distance of 0.66 mm. Objectives 40x Plan Fluorite oil immersion objective with 1.3 numerical aperture. INS-OBJ-40-130-0 Working distance of 0.24 mm. 60x Plan Apochromat oil immersion objective with 1.4 numerical aperture. INS-OBJ-60-140-0 Working distance of 0.13 mm.

Step 4.	Select the required incubator	
	Description	Order Code
Incubators	Stage-top incubator with humidity module and digitally controlled ${\rm CO_2}$ regulation using a pure ${\rm CO_2}$ source	INS-INC-HUM-CO2-D
	Stage-top incubator with humidity module and manual valve controlled ${\rm CO_2}$ regulation using a pure ${\rm CO_2}$ source	INS-INC-HUM-CO2-M
	Stage-top incubator with humidity module and manual valve controlled CO ₂ regulation using a a pre-mix air/CO ₂ cylinder	INS-INC-HUM-PRE-M

Step 5a.	Select the required incubator sample holders	
	Description	Order Code
	One position. 1x3 inch chamber slide holder	MSD-INCB-1XGS-M
	One position. 35 mm Petri-dish holder	MSD-INCB-1X35-M
	Two position. 35 mm Petri-dish holder	MSD-INCB-2X35-M
	One position. 1x3 inch chamber slide and #2 35 mm Petri-dish holder	MSD-INCB-GS35-M
Incubator	Open frame for multi well plates, suitable for oil immersion objectives	MSD-INCB-MW-OIL
Sample Holders	Two position. 1x3 inch chamber slide holder	MSD-INCB-2XGS-M
	One position. Lab-Tek 1x2 inch chambered cover glass holder	MSD-INCB-1XLBTK-M
	Two position. Lab-Tek 1x2 inch chambered cover glass holder	MSD-INCB-2XLBTK-IIM
	#1 Lab-Tek II $1x$ 2 inch chambered cover glass and $#1$ 50/60 mm Petri-dish holder	MSD-INCB-LBTK-II-60M
	#2 Lab-Tek 1x2 inch chambered cover glass holder	MSD-INCB-2XLBTK-M
	#1 Lab-Tek II 1x2 inch chambered cover glass holder	MSD-INCB-1XLBTK-IIM

Step 5b.	Select the required incubator accessories		
	Description	Order Code	
	Magnetic holder for 35 mm petri dish.	MSD-INCB-35-TL-M	
Incubator Accessories	Lid with thermocouple for local / sample temperature recording at the level of the sample.	MSD-INCB-SENSOR	
Accessories			



Order Today

Need more information? At Andor we are committed to finding the correct solution for you. With a dedicated team of technical advisors, we are able to offer you one-to-one guidance and technical support on all Andor products. For a full listing of our local sales offices, please see: andor.com/contact

Our regional headquarters are:

Europe

Belfast, Northern Ireland Phone +44 (28) 9023 7126 Fax +44 (28) 9031 0792

North America

Concord, MA, USA Phone +1 (860) 290 9211 Fax +1 (860) 290 9566

Japan

Tokyo Phone +81 (3) 6732 8968 Fax +81 (3) 6732 8939

China

Beijing Phone +86 (10) 5884 7900 Fax +86 (10) 5884 7901

Items shipped with BC43

Base unit, cables and accessories (model as

PC Workstation and accessories Fusion and Imaris for BC43 software User guides in electronic format Quick start guide Up to 5 microscope objectives 3D navigation joystick Microscope slides

Operating & Storage Conditions:

- Indoor use only
- Operating Temperature: 18°C to +25°C ambient
- Storage Temperature: 0°C to 50°C
- Relative Humidity: <70% (non-condensing)
- Size/Weight (BC43)
- $W \times D \times H: 505 \times 633 \times 443 \text{ mm}$ and 65 kg

Power Requirements:

- Mains Supply: 100 240 VAC, 50 60 Hz. System Power Consumption (Typ./ Max.): 75 W/ 90 W

Cover Image: FluoTissue mouse intestine section. Blood vessels labeled with AlexaFluor(R) 488 and Lymphatic vessels with AlexaFluor(R) 633. Image captured at 10x magnification with a 4x4 montage and stitched within Fusion. Imaged to a depth of 467 µm with a 1.99 µm step (total 235 optical sections). Sample sourced from SUNJin Lab. Image credits: Geraint Wilde, Andor Technology.

Footnotes

- 1. Figures are typical unless otherwise stated.
- 2. Quantum efficiency as supplied by the sensor manufacturer.
- 3. Imaris for BC43 supplied, additional modules will require a separate license.

Laser Safety Information

- 1. It is very hard to access the laser beam with the eye without using a reflective surface to redirect it.
- 2. Class 2 means that the eye aversion response protects against the laser radiation and you have to deliberately stare at it to cause damage. A typical Class 2 product is a laser pointer.







